

STANDARD FEATURES

- Base Assembly is Fabricated of Steel Channel, Full Rear to Tongue Eye, with Integral Crossmembers
- Single Axle, 20,000 lb (9,072 kg) Capacity, Equipped with Full Air Brakes
- Leaf Spring Suspension
- Stiff Leg for Storage; Steel Fenders
- Lighting Meets US FMVSS
- Two (2) 425/65R22.5 Load Range "L" Jumbo Flotation Tires; 22.5 by 12.25 Disc Wheels
- Diesel Engine, 110 HP @ 2,500 RPM, Four Cylinder
- 50 GAL (189 L) Fuel Tank
- Stainless Steel Water Tank, 304 Stainless Steel
- Electronic Water Level Sensor is Provided
- Four Lifting Eyes Provided for Removing Tank When Empty
- Four-Stage, High-Pressure Centrifugal Water Pump
- Top or Bottom Fill Available on Water Tank with Strainer
- Hose Reel – Electric Rewind with 150 ft (45.7 m) Length of 1 in (25 mm) Diameter Hose, Non-Conductive
- Tool Storage Compartment
- Access Steps to Reach Access Dome
- Hand-Held Wash Gun
- Throttle Mode Selector
- Constant Resistivity Monitor Provided in Tank
- Portable Resistivity Tester
- Automatic Low Water Shutdown
- Painted White
- Two (2) Operator's and Two (2) Maintenance/ Parts Manuals

OPTIONS

- Second Wash Gun Assembly, Includes Reel, Hand-Held Wash Gun, and Throttle System
- Spare Wash Gun Assembly
- Spare Water Nozzle(s)
- Increased Flow Nozzle
- Additional Portable Resistivity Tester
- Trailer Grounding System
- Wash Gun Grounding System
- Extra Manuals
- Mild Steel Tank
- Auxiliary Input System
- Auxiliary Output System
- Spare Tire and Wheel

GENERAL SPECIFICATIONS

Trailer Chassis – Single Axle Rating	20,000 lb	9,072 kg
Tank Capacity		
Model HLIW1200T	1,200 GAL	4,542 L
Model HLIW1600T	1,600 GAL	6,057 L
Operating Range with 1/4" (6.4 mm) Nozzle- Each Gun Flow Adjustable to Maximum Each Gun Pressure Adjustable to Maximum	44 GPM	167 LPM
Single Wash Gun Each	800 PSI	5,515 kPa
Two Wash Gun Each	650 PSI	4,481 kPa
Overall Dimensions (H x W x L)	96" H x 88" W x 208" L	244 cm x 224 cm x 528 cm
Weight (without water)		
Model HLIW1200T:	7,600 lbs	
Model HLIW1600T:	7,740 lbs	

Altec Aerial Devices meet or exceed all applicable ANSI Standards as of the date of manufacture. Altec reserves the right to improve models and change specifications without notice or obligation.

Altec Sales and Service



Manufacturing and Service Facilities Located
Throughout the United States and Canada

Altec Industries, Inc.

Post Office Box 10264
Birmingham, Alabama 35202
Phone 205/991-7733
Fax 205/991-9993



Altec HLIW1200/1600-T Hotline Insulator Washer Trailer



- Usable by Itself or in Conjunction with Aerial Device
- Water Tank Capacity to 1600 GAL (6,057 L)
- Quick, Easy Set-up
- Automatic Low Water Shutdown
- Onboard Resistivity Monitoring